

Product Description

EXCEPTIONAL[®] Metals Downspouts are available with an open or closed face. Both open and closed face downspouts are available in standard 10' lengths.

- Custom sizes and assemblies are available.
- A- and B-Style Elbows, Square-To-Round Adaptors, and Drop/Outlets available.
- LEED[®] compliant.

Open-Face Downspouts

- Help eliminate blockage due to ice and debris build-up.
- Will nest together by cutting a 1" notch out of each side of the receiving piece.

Closed-Face Downspouts

- Standard 24-gauge downspouts feature a Pittsburgh seam for a professional finish that also eliminates the need for rivets.
- Tapered ends nest together up to 3" and eliminate field notching and crimping.


Downspout



Square-To-Round
Adaptor



Drop/Outlet



Note: The quantity and size of the downspout is the responsibility of the contractor or design professional.

Installation

1. Install in accordance with EXCEPTIONAL Metals' Details #2080, #2085, and #2086.
2. Any deviation from the requirements set forth in detail drawings must be pre-approved, in writing, by the EXCEPTIONAL Metals' Technical Department.

Warranty

EXCEPTIONAL Metals offers a finish and substrate warranty. Contact the membrane manufacturer for any additional warranty that may be offered.

Technical Services

Product samples, detail sheets, color chips, and color chart are available for your submittal package. For assistance with questions or submittals, contact your local representative or call EXCEPTIONAL Metals.

Material	Gauge	Finish
Aluminum	.040	Mill or Kynar [®]
Stainless Steel	24-gauge	N/A
Bonderized Steel	24-gauge	N/A
Galvalume [®]	24-gauge	Mill or Kynar [®]
Copper	16 oz.	Mill

For more information give us a call
or visit our website today.

800-248-0280 • exceptionalmetals.com