




# EXCEPTIONAL<sup>®</sup> Metals

APPLY BEAD OF URETHANE  
SEALANT OVER RIB BEFORE  
APPLYING RIB COVER

FILL BOTH ENDS W/  
URETHANE SEALANT



FIELD CUT PANEL RIBS  
AND BEND PAN OVER  
AT TRANSITION.

12

EM LOKSEAM PANEL

UL90 CLIP [HW-6400]

1/8 x 3/8 POP RIVET  
[FASTENER #14A]  
(3) PER RIB COVER

EM LOKSEAM RIB COVER  
[FL-565] (FIELD NOTCH  
AS REQ'D. & BEND TO  
PROPER ANGLE)

UL90 CLIP [HW-6400]

12-11 x 1 PANCAKE HEAD  
SELF-TAPPER [FASTENER #13A]  
(2) PER CLIP

EM LOKSEAM PANEL

12-11 x 1 PANCAKE HEAD  
SELF-TAPPER [FASTENER #13A]  
(2) PER CLIP

MOISTURE BARRIER  
(NOT BY EXCEPTIONAL METALS)

5/8" PLYWOOD MIN.  
(NOT BY EXCEPTIONAL METALS)

MOISTURE BARRIER  
(NOT BY EXCEPTIONAL METALS)

5/8" PLYWOOD MIN.  
(NOT BY EXCEPTIONAL METALS)

O/O DIMENSION  
(SEE PLAN)

REVISED: 07/16/2018

STANDING SEAM ROOF PANELS

AUTHOR BVANOCHT

EM LOKSEAM<sup>®</sup>

SCALE: NONE

EAVE TRANSITION