



EXCEPTIONAL® HT Primer

Product Data Sheet



Product Description

EXCEPTIONAL HT (high temperature) Primer is a solvent-based primer composed of a blend of natural resins and synthetic rubber. EXCEPTIONAL HT Primer is designed to enhance the adhesion of EXCEPTIONAL HT underlayment to a variety of surfaces such as structural concrete, gypsum, lightweight concrete, wood and masonry.

Ordering

EXCEPTIONAL HT Primer is ordered in individual 5-gallon buckets. Each bucket covers approximately 375 to 625 square feet.

- 33-lb. bucket (Item #1349).

Storage and Handling

- Product can be stored for up to 36 months in original sealed containers. Store in a cool, well-ventilated area between 14 – 75° F (-10° – 23° C). Keep away from any source of heat, dampness, humidity, oxidizing agents or direct sunlight.
- Product is flammable prior to curing. Keep away from open flames and any other source of ignition.

Precautions

- Read Safety Data Sheets (SDS) prior to using.
- Wear proper personal protective equipment, such as gloves and eye protection, per the SDS.

Installation

1. Limitations
 - The minimum ambient and surface temperature before application should be 14° F (-10° C) and rising.
 - Apply to a clean and structurally sound substrate.
2. Shake product thoroughly prior to application.
3. Apply to deck at a rate of 75 – 125 sq. ft. per gallon using either a brush or roller.
4. Do not install EXCEPTIONAL HT underlayment until EXCEPTIONAL HT Primer has completely dried. Do not accelerate drying by use of heat.

EXCEPTIONAL HT PRIMER	
Specific gravity at 68° F	6.59 lbs./gal ¹
Color	Red
Solids by weight	24% ¹
Viscosity, Brookfield at 77° F	200 cP ¹
Set time	Between 15 and 60 minutes, depending on temperature and quantity applied.
Application temperature	14° F (-10° C) and rising
Coverage	75 – 125 sq. ft. per gallon
¹ Nominal.	

Cleaning

Tools can be cleaned with petroleum solvents such as mineral spirits, Varsol™, xylene, etc.

For more information give us a call or visit our website today.

800-248-0280 • exceptionalmetals.com

¹ "EXCEPTIONAL" is a registered trademark.