

Product Data Sheet



DefendEX™ SS2000 Fixed Clip

Clip Style

Galvanized Steel

Item Number

W6810C0624

Description

DefendEX™ SS2000 Fixed Clip is specially designed to be used in the attachment of the DefendEX SS2000 Standing Seam Roof Panel. The clip design allows the upper tab to mechanically integrate into the double lock seam.

Material only warranty available.

Method of Application

1. Position the clips flush against the vertical seam.
2. Attach the clips to the roof deck using approved fasteners.
3. Position the adjacent panel flush against the installed clip.
4. Secure the panel by folding the outer vertical female leg 90° under the head of the male leg at the clip location.

NOTE: Install assembly according to the *Metal Roofing Design Guide* and the *Metal Roofing System Application Guide* found on the [Exceptional Metals website](#). Follow approved installation details.

Storage

Store in unopened, original containers, protected from the weather.

Packaging

1000 clips per carton

Precautions

- Eye protection must be worn during the installation of fasteners.
- Do not overdrive or underdrive fasteners.
- Only designed to anchor SS2000 standing seam roof panels.
- Cannot use fasteners larger than #12.

Stocking Location: Anoka, MN



This sheet is meant to highlight Exceptional Metals products and specifications and is subject to change without notice. Amrize™ takes responsibility for furnishing quality materials that meet published Exceptional Metals product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Amrize nor its representatives practice architecture. Amrize offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Amrize accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Amrize representative is authorized

Product Data	
Property	Value
Material	G90 Galvanized Steel
Material Thickness	24 ga; 0.023 - 0.025 in. (0.58 - 0.64 mm)
Base	3.0 x 0.95 in. (76.20 x 24.13 mm)
Tab	1.50 x 2.05 in. (38.10 x 52.07 mm)
Hole Diameter	0.25 in. (6.35 mm)

Contact EXCEPTIONAL Metals Technical Services at (866) 337-4599 for further information.

EXCEPTIONAL Metals is a brand of Amrize Building Envelope LLC.

"EXCEPTIONAL", "DefendEX", and Amrize are trademarks in the Amrize portfolio. All other trademarks are property of their respective owners.

Phone: (866) 337-4599
exceptionalmetals.com