

Gutter

Description:

Four box-style profiles in three sizes each. Support straps are provided based on 30" centers.

- Front edge of gutter is 2" lower than the back edge.
- Internal splice plates eliminate the need to completely rivet sections together.
- Riveted inside and outside miters can be fabricated to any angle.
- Roof flanges can be bent to accommodate various roof pitches or eliminated altogether.
- Custom sizes and profiles are available.



DX-Style

EX-Style



LX-Style


MX-Style

Energy Efficiency:

LEED® and ENERGY STAR® compliant.

Installation:

1. Install in accordance with EXCEPTIONAL® Metals Details #2091 and #3025.
2. Any deviation from the requirements set forth in detail drawings must be pre-approved, in writing, by the EXCEPTIONAL Metals Technical Department.




Warranty:

EXCEPTIONAL Metals offers a finish and substrate warranty. Contact the membrane manufacturer for any additional warranty that may be offered.

Technical Services:

Product samples, detail sheets, color chips, and color chart are available for your submittal package. For assistance with questions or submittals, contact your local representative or call EXCEPTIONAL Metals.



| Material | Gauge | Finish |
|------------------|-------------|----------------|
| Aluminum | .040 / .050 | Mill or Kynar® |
| Stainless Steel | 24-gauge | N/A |
| Bonderized Steel | 24-gauge | N/A |
| Galvalume® | 24-gauge | Mill or Kynar® |
| Copper | 16 oz. | Mill |

Note: The quantity and size of gutters are the responsibility of the contractor or design professional.